

Cold water high pressure washers

G135-145-151-161-155-165



Standard professional hose reel where it is possible to wind easily and rapidly the hose in order to protect it from any damage (plus version).



8 m H.P. hose with screw coupling (12m PLUS Version)



Gun with athermic extension



Lance with adjustable head and Turbo nozzle



Thanks to the particular chemical injection system and the two tanks of this machine, it is possible to deliver and adjust the quantity of two different detergents.



The starting handgrip, the detergent tap and the inlet water connection are placed on the front side of machine.



With a simple lever placed next to the hose reel, the hose can be blocked at the desired lengths.



Standard supports for gun, lance and lance with rotating nozzle to have them ready to be used.



Thanks to electric cable reel, it is possible to rewind the feeding cable when working operations are finished.

Technical characteristics

- **AUTOMATIC TOTAL STOP**
The machine goes off automatically when the trigger gun is released. Increases the life of the pump.
- **PUMP**
Axial pump with head in aluminium or brass in AO models.
- **STAINLESS STEEL PISTONS**
Pistons with excellent mechanical characteristics.
- **MOTOR**
Electric induction motor, two pole, continuous duty. Maintenance free.
- **THERMAL CUTOUT**
The motor is protected from excessively high temperatures by a thermal cutout.
- **GAUGE (PW-C23 PI1508AO-M / PI1610AO-M)**
Professional gauge to constantly check the working pressure.

Code	Model	Remote control	Pressure (bar)	Flow rate (l/h)	Voltage (Ph-V-Hz)	Absorbed power (kW)	Max water inlet temp. (°C)	Hose (m)	Electric cable (m)	Weight (Kg)	Dimensions (cm)
IDAF 94234	G 135-C I 1307A-M	Total Stop	130	390	1-230-50	1,9	50	8	5	16	38x33x84
IDAF 94236	G 145-C I 1408A-M	Total Stop	140	460	1-230-50	2,3	50	8	5	18,5	38x33x84
IDAF 94238	G151-C I1508A-M	Total Stop	150	500	1-230-50	2,5	50	8	5	22	38x33x84
IDAF 94240	G 161-C I1610A-M	Total Stop	160	600	1-230-50	3	50	8	5	23	38x33x84
IDAF 94242	G 155-C I 1508AO-M	Total Stop	150	500	1-230-50	2,5	50	8	5	23	38x33x84
IDAF 94244	G 165-C I 1610AO-M	Total Stop	160	600	1-230-50	3	50	8	5	24	38x33x84

All versions are also available in the Plus version which, as well as the standard accessories, also includes 12 m H.P. hose with screw coupling and hose reel.

